





	NUT INSERTS - Steel					
	Thread Size	Grip Range	Drill Size			
3832-632	6-32unc	0.094-0.156	#2			
3832-832	8-32unc	0.094-0.156	1/4"			
3832-1024	10-24unc	0.094-0.156	9/32"			
3832-1032	10-32unf	0.094-0.156	9/32"			
3832-1420	1/4-20unc	0.094-0.156	25/64"			
3832-51618	5/16-18unc	0.094-0.156	1/2"			
3832-3816	3/8-16unc	0.094-0.156	9/16"			
	FLUSH RIVET NUTS - Steel					
	Thread Size	Grip Range	Drill Size	Diameter	Diameter	
4032-632	6-32unc	0.020 to 0.080"	1/4"	0.287"	0.249"	
4032-832	8-32unc	0.020 to 0.080"	1/4"	0.287"	0.249"	
4032-1024	10-24unc	0.020 to 0.130"	9/32"	0.320"	0.280"	
4032-1032	10-32unf	0.020 to 0.130"	9/32"	0.320"	0.280"	
4032-1420	1/4-20unc	0.030 to 0.165"	3/8"	0.415"	0.374"	
4032-51618	5/16-18unc	0.030 to 0.165"	1/2"	0.540"	0.499"	
4032-3816	3/8-16unc	0.030 to 0.165"	1/2"	0.540"	0.499"	
4032-M4	M4x0.7	0.020 to 0.080"	1/4"	0.287"	0.249"	
4032-M5	M5x0.8	0.020 to 0.130"	9/32"	0.320"	0.280"	
4032-M6	M6x1.0	0.030 to 0.165"	3/8"	0.415"	0.374"	
4032-M8	M8x1.25	0.040 to 0.200"	1/2"	0.540"	0.499"	
	FLUSH RIVET NUTS - Aluminum					
	Thread Size	Grip Range	Drill Size	Diameter	Diameter	
4132-632	6-32unc	0.020 to 0.080"	1/4"	0.287"	0.249"	
4132-832	8-32unc	0.020 to 0.080"	1/4"	0.287"	0.249"	
4132-1024	10-24unc	0.020 to 0.130"	9/32"	0.320"	0.280"	
4132-1032	10-32unf	0.020 to 0.130"	9/32"	0.320"	0.280"	
4132-1420	1/4-20unc	0.030 to 0.165"	3/8"	0.415"	0.374"	
4132-51618	5/16-18unc	0.030 to 0.165"	1/2"	0.540"	0.499"	
4132-3816	3/8-16unc	0.030 to 0.165"	1/2"	0.540"	0.499"	



	FLANGED RIVET NUTS - Steel						
	Thread Size	Grip Range	Drill Size	Head Diameter	Head Height	Body Diameter	Flange Diameter
4232-632	6-32unc	0.010 to 0.075"	#12	0.325"	0.032"	0.189"	0.325"
4232-832-1	8-32unc	0.010 to 0.075"	#2	0.357"	0.032"	0.221"	0.357"
4232-832-2	8-32unc	0.075 to 0.120"	#2	0.357"	0.032"	0.221"	0.357"
4232-1024-1	10-24unc	0.010 to 0.080"	1/4"	0.406"	0.038"	0.250"	0.406"
4232-1024-2	10-24unc	0.080 to 0.130"	1/4"	0.406"	0.038"	0.250"	0.406"
4232-1032-1	10-32unf	0.010 to 0.080"	1/4"	0.406"	0.038"	0.250"	0.406"
4232-1032-2	10-32unf	0.080 to 0.130"	1/4"	0.406"	0.038"	0.250"	0.406"
4232-1420-1	1/4-20unc	0.020 to 0.080"	Q	0.475"	0.058"	0.332"	0.475"
4232-1420-2	1/4-20unc	0.080 to 0.140"	Q	0.475"	0.058"	0.332"	0.475"
4232-1420-3	1/4-20unc	0.140 to 0.200"	Q	0.475"	0.058"	0.332"	0.475"
4232-51618-1	5/16-18unc	0.030 to 0.125"	Z	0.665"	0.062"	0.413"	0.665"
4232-51618-2	5/16-18unc	0.125 to 0.200"	Z	0.665"	0.062"	0.413"	0.665"
4232-3816-1	3/8-16unc	0.030 to 0.115"	12.5mm	0.781"	0.088"	0.490"	0.781"
4232-3816-2	3/8-16unc	0.115 to 0.200"	12.5mm	0.781"	0.088"	0.490"	0.781"
	FLANGED RIVET NUTS - Aluminum						
	Thread Size	Grip Range	Drill Size	Head Diameter	Head Height	Body Diameter	Flange Diameter
4332-632	6-32unc	0.010 to 0.075"	#12	0.325"	0.032"	0.189"	0.325"
4332-832-1	8-32unc	0.010 to 0.075"	#2	0.357"	0.032"	0.221"	0.357"
4332-832-2	8-32unc	0.075 to 0.120"	#2	0.357"	0.032"	0.221"	0.357"
4332-1024-1	10-24unc	0.010 to 0.080"	1/4"	0.406"	0.038"	0.250"	0.406"
4332-1024-2	10-24unc	0.080 to 0.130"	1/4"	0.406"	0.038"	0.250"	0.406"
4332-1032-1	10-32unf	0.010 to 0.080"	1/4"	0.406"	0.038"	0.250"	0.406"
4332-1032-2	10-32unf	0.080 to 0.130"	1/4"	0.406"	0.038"	0.250"	0.406"
4332-1420-1	1/4-20unc	0.020 to 0.080"	Q	0.475"	0.058"	0.332"	0.475"
4332-1420-2	1/4-20unc	0.080 to 0.140"	Q	0.475"	0.058"	0.332"	0.475"
4332-1420-3	1/4-20unc	0.140 to 0.200"	Q	0.475"	0.058"	0.332"	0.475"
4332-51618-1	5/16-18unc	0.030 to 0.125"	Z	0.665"	0.062"	0.413"	0.665"
4332-51618-2	5/16-18unc	0.125 to 0.200"	Z	0.665"	0.062"	0.413"	0.665"
4332-3816-1	3/8-16unc	0.030 to 0.115"	12.5mm	0.781"	0.088"	0.490"	0.781"
4332-3816-2	3/8-16unc	0.115 to 0.200"	12.5mm	0.781"	0.088"	0.490"	0.781"


317.773.1668 317.773.1690fx
sales@crossroad.bz
www.crossroadistributorsource.com



	FLANGED KNURLED RIVET NUTS - Steel						
	Thread Size	Grip Range	Drill Size	Head Diameter	Head Height	Body Diameter	Flange Diameter
4432-632-1	6-32unc	0.020 to 0.080"	17/64"	0.392"	0.028"	0.264"	0.392"
4432-632-2	6-32unc	0.080 to 0.130"	17/64"	0.392"	0.028"	0.264"	0.392"
4432-832-1	8-32unc	0.020 to 0.080"	17/64"	0.392"	0.028"	0.264"	0.392"
4432-832-2	8-32unc	0.080 to 0.130"	17/64"	0.392"	0.028"	0.264"	0.392"
4432-1024-1	10-24unc	0.020 to 0.130"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-1024-2	10-24unc	0.130 to 0.225"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-1032-1	10-32unf	0.020 to 0.130"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-1032-2	10-32unf	0.130 to 0.225"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-1420-1	1/4-20unc	0.027 to 0.165"	25/64"	0.500"	0.028"	0.390"	0.500"
4432-1420-2	1/4-20unc	0.165 to 0.260"	25/64"	0.500"	0.028"	0.390"	0.500"
4432-51618-1	5/16-18unc	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-51618-2	5/16-18unc	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-3816-1	3/8-16unc	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-3816-2	3/8-16unc	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-M4-1	M4x0.7	0.020 to 0.080"	17/64"	0.392"	0.028"	0.264"	0.294"
4432-M4-2	M4x0.7	0.080 to 0.130"	17/64"	0.392"	0.028"	0.264"	0.294"
4432-M5-1	M5x0.8	0.020 to 0.130"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-M5-2	M5x0.8	0.130 to 0.225"	19/64"	0.417"	0.028"	0.295"	0.417"
4432-M6-1	M6x1.0	0.027 to 0.165"	25/64"	0.500"	0.028"	0.390"	0.500"
4432-M6-2	M6x1.0	0.165 to 0.260"	25/64"	0.500"	0.028"	0.390"	0.500"
4432-M8-1	M8x1.25	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-M8-2	M8x1.25	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-M10-1	M10x1.5	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4432-M10-2	M10x1.5	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"

317.773.1668 317.773.1690fx
 sales@crossroad.bz
 www.crossroadistributorsource.com



	FLANGED KNURLED RIVET NUTS - Aluminum						
	Thread Size	Grip Range	Drill Size	Head Diameter	Head Height	Body Diameter	Flange Diameter
4532-632-1	6-32unc	0.020 to 0.080"	17/64"	0.392"	0.028"	0.264"	0.392"
4532-632-2	6-32unc	0.080 to 0.130"	17/64"	0.392"	0.028"	0.264"	0.392"
4532-832-1	8-32unc	0.020 to 0.080"	17/64"	0.392"	0.028"	0.264"	0.392"
4532-832-2	8-32unc	0.080 to 0.130"	17/64"	0.392"	0.028"	0.264"	0.392"
4532-1024-1	10-24unc	0.020 to 0.130"	19/64"	0.417"	0.028"	0.295"	0.417"
4532-1024-2	10-24unc	0.130 to 0.225"	19/64"	0.417"	0.028"	0.295"	0.417"
4532-1032-1	10-32unf	0.020 to 0.130"	19/64"	0.417"	0.028"	0.295"	0.417"
4532-1032-2	10-32unf	0.130 to 0.225"	19/64"	0.417"	0.028"	0.295"	0.417"
4532-1420-1	1/4-20unc	0.027 to 0.165"	25/64"	0.500"	0.028"	0.390"	0.500"
4532-1420-2	1/4-20unc	0.165 to 0.260"	25/64"	0.500"	0.028"	0.390"	0.500"
4532-51618-1	5/16-18unc	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4532-51618-2	5/16-18unc	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"
4532-3816-1	3/8-16unc	0.027 to 0.150"	17/32"	0.685"	0.032"	0.530"	0.685"
4532-3816-2	3/8-16unc	0.150 to 0.312"	17/32"	0.685"	0.032"	0.530"	0.685"
4532-M6-1	M6x1.0	0.027 to 0.165"	25/64"	0.500"	0.028"	0.390"	0.500"

317.773.1668 317.773.1690fx
 sales@crossroad.bz
 www.crossroaddistributorsource.com